

Analyses and Interpretations of Structural Health Monitoring Data on Reinforced Concrete Buildings: A Critical Review

^{1,2}Atoyebi Olumoyewa Dotun, ²Afolayan Joseph O. and ²Arum Chinwuba
¹Department of Civil Engineering, Landmark University, Omu-Aran, PMB 1001,
Kwara State, Nigeria
²Department of Civil Engineering, Federal University of Technology, Akure, Nigeria
atoyebi.olumoyewa@lmu.edu.ng, +2348036350086

Abstract: Existing reinforced concrete buildings have experienced different forms of failures due to limitations in analysing and interpreting the information derived from the study of their behaviour under loading. Structural Health Monitoring (SHM) which is the study of the way structures relate with different loading conditions using equipment and machine that can read data without affecting the existence of the structure has been analysed in times past using different methods and there is need to bring in probabilistic methods in terms of reliability-based paradigm, i.e., reliability theory to analyse and interpret SHM data. Reliability method expresses logical handling of structural design uncertainties in the assessment of the structures safety and serviceability, it provides a very powerful tool for SHM to add probabilistic structural evaluation function that current SHM applications and statistical analysis packages do not have. This review study looks into different ways SHM data have been analysed and the need to introduce probabilistic approach to SHM.

Key words: Structural health monitoring, non-destructive test, reliability theory, reinforced concrete building, limitations, statistical analysis

INTRODUCTION

Reinforced Concrete Buildings (RCB) undergoing construction to a greater extent can be assumed safe using the present day design requirements and assumptions, structural fitness is therefore guaranteed for this category but for existing buildings; there is need for timely monitoring methods to acquire data which will help to determine their state of fitness. Presently in the construction world, a great sensitization is occurring towards the usefulness of having systems in aerospace, civil and mechanical structures which can state the cause of damages. This damage prognosis system in a structure would give the user information on the structure's health, accurate details of upcoming damage and the structure's life span (Farrar and Worden, 2006). The assessment of existing buildings is of much importance and of great concern to the construction world, users also daily get involved in a new way of putting these structures to use and a standard is yet to be developed for the examination and retrofitting of existing RCB (Holicky *et al.*, 2014; Rens *et al.*, 1997). The structural health of existing buildings poses much treat to our

environment due to inadequate methods of acquiring data on the structures responses to loads, environmental impacts and age. For an effective SHM process in terms of reliability-based paradigm, there is need to focus on the mode of testing structures both in real life and laboratory conditions/environment, equipment used, type of data to be taken, how they are analysed and used in reliability studies.

Literature review

Non-destructive testing: Recent innovations of codes (BSI., 1998) provide clear rules for assessing the safety and conduct of static strengthening on existing buildings. Inventions also have provided a way out in non-destructive methods or techniques to assess existing buildings. Non-Destructive Inspections (NDI) are ways of assessing a structure working with attached or embedded equipment which does not in any way affect the state of the structure (Elsener *et al.*, 2003a, b; Chang *et al.*, 2003). Non-Destructive Testing (NDT) is a maturing technology field that reveals, study and analyse defects in engineering structures using mostly physics-based techniques (Ibrahim, 2014, 2016). NDT has been defined has methods of examination without having an adverse

effect on the examined system. These methods are now top on the list in the area of reliability and effectiveness as it offers a better choice in testing *in situ* (Shaw and Xu, 1997). NDT techniques measures responses given by a structure to interferences induced using mechanical, chemical and electromagnetic energies. NDT techniques has gone through periods of revolution from unassisted visual and aural (acoustic) inspection (ACI Committee 228, 1998; Park *et al.*, 2001; Estes and Frangopol, 2003; Gattulli and Chiramonte, 2005; Alani *et al.*, 2013, 2014) to advanced methods of lighting to aid visual inspections and tap-hammers to detect more subtle acoustic (and hence localised stiffness) changes (Ibrahim, 2014). Different researchers in different parts of the world have worked on numerous NDT methods which are visual inspection (Perenchio, 1989; Anonymous, 2001), chain drag (ASTM., 2003, 2009; Barnes and Trottier, 2000; Gucunski and NRC, 2013; ASTM, 1997; Barnes *et al.*, 2008), coin tap test (McCann and Forde, 2001; Cawley, 1991; Wu and Siegel, 1999; Cawley and Adams, 1988), acoustic emission (Rens *et al.*, 1997; Carlos *et al.*, 2000; Holford and Lark, 2005; Holford *et al.*, 2001), impact echo testing (Sansalone, 1997; Sansalone and Street, 1997; Lin and Sansalone, 1993, 1994, 1996; Cheng and Sansalone, 1993; Lin and Su, 1996; Azari *et al.*, 2014), sonics (ACI Committee 228, 1998; McCann and Forde, 2001; Binda *et al.*, 2001, 2003; Colla *et al.*, 1997), ultrasonic NDT (ACI Committee 228, 1998; Azari *et al.*, 2014; Afshari *et al.*, 1996; Bogas *et al.*, 2013; ASTM., 2009; Schickert, 2005; Shah *et al.*, 2013; Shokouhi *et al.*, 2013; Taffe and Wiggenhauser, 2006), impulse response (ACI Committee 228, 1998; Davis, 2003; Turner, 1997), ground penetrating radar (ACI Committee 228, 1998; Barnes *et al.*, 2008; Orlando *et al.*, 2010; Alani *et al.*, 2013;

Yehia *et al.*, 2014; Perez-Gracia *et al.*, 2008; Diamanti *et al.*, 2008; Solla *et al.*, 2012; Hugenschmidt and Mastrangelo, 2006; Chang *et al.*, 2009), conductivity (McCann and Forde, 2001; Colla *et al.*, 1997; Garboczi *et al.*, 1995; Whittington *et al.*, 1981), coring (Gucunski and NRC., 2013; Suzuki *et al.*, 2010; Scott *et al.*, 2003; ASTM., 2003), electrical resistivity (Gucunski and NRC., 2013; Ryan *et al.*, 2013; Lataste *et al.*, 2003; Saleem *et al.*, 1996; Polder, 2001), proof load test (Casas and Gomez, 2013; Faber *et al.*, 2000; Saraf *et al.*, 1996; Fu and Tang, 1995), infrared thermography (ACI Committee 228, 1998; Gucunski and NRC., 2013; McCann and Forde, 2001; Clark *et al.*, 2009; Buyukozturk, 1998; Stanley and Balendran, 1994), half-cell potential (Elsener *et al.*, 2003a, b; ACI Committee 228, 1998; ASTM., 1999; Elsener *et al.*, 2003a, b; Elsener, 2001; Ohtsu *et al.*, 1997; Clemea *et al.*, 1992), radiography (Ibrahim, 2014; Song and Saraswathy, 2007; Malhotra, 1976; Naik *et al.*, 2004), dynamic/vibration testing (Bedon and Morassi, 2014; Cunha *et al.*, 2013; Samman and Biswas, 1994; Hashim *et al.*, 2013; Ismail *et al.*, 2011; Gentile, 2006; Reynolds, 2008; Caetano *et al.*, 2015; De Roeck *et al.*, 2000; Salawu and Williams, 1995), Schmidt rebound hammer (Szilagyi *et al.*, 2011; Breyse, 2012; Kim *et al.*, 2009; Anonymous, 2001; Basu and Aydin, 2004; Samman and Biswas, 1994). These NDT methods have limitations which are hindrances to their usage (Rehman *et al.*, 2016) as iterated in Table 1.

The process of making use of non-destructive techniques and equipment to observe and study a structure within a time frame is known as SHM. Inspections in RCB is a periodic exercise, the transition from NDI to SHM is a transition from the traditional “time-based” to the emerging “condition-based” maintenance (Mandache *et al.*, 2011).

Table 1: Limitations of non destructive methods

NDT methods	Limitations
Impact echo (Sansalone, 1997; Azari <i>et al.</i> , 2014; Sadowski <i>et al.</i> , 2016)	High temperature of asphalt concrete overlay not detectable Low viscous material is difficult to detect Signals are affected greatly by deck boundaries Marking the boundaries of delimited area may not be possible without dense grids Detection is only possible for loosely bonded overlay to the deck Interference of boundary on signal is more prominent on limited dimensional elements like girders and piers
Impulse response (Davis, 2003; Sadowski <i>et al.</i> , 2016; Maierhofer <i>et al.</i> , 2010)	Selection of test points determines reliable data interpretation Inability to detect small defects Unavailability of automated apparatus
Acoustic emission (Holford and Lark, 2005; Suzuki <i>et al.</i> , 2010; Behnia <i>et al.</i> , 2014; Langenberg <i>et al.</i> , 2010)	It works with a background noise Its analysis application to real structure is difficult Well defined procedure for all types of bridges is not available
Ultrasonic pulse velocity (Bogas <i>et al.</i> , 2013; Breyse, 2012; Jain <i>et al.</i> , 2013)	This method is time consuming Detection of shallow defects may not occur Coupling of the sensor unit determines the quality of data in a great deal and there is difficulty in coupling on rough surfaces Very close grid spacing is needed Lower frequencies may cause incomplete detection

Table 1: Continue

NDT methods	Limitations
Ground penetrating radar (Alani <i>et al.</i> , 2013a, 2014; Barnes and Trotter, 2000)	Too costly to use Difficult to detect moisture completely frozen Strength, modulus and some mechanical properties estimation is almost impossible GPR data are affected by extreme cold conditions and acquired signal influenced. Effects like corrosion or rebar section loss are difficult to read
Half-cell potential (Elsener <i>et al.</i> , 2003; Elsener, 2001; Wankhade and Landage, 2013)	Isolating layers such as paint, coating and asphalt are difficult to read Depth data is difficult to correct Temperature higher than 2°C is required Concrete cover depth influence unknown Method can't be used for moisture or salt content calculation
Infrared thermography (Clark <i>et al.</i> , 2009; Buyukozturk, 1998; Tortora <i>et al.</i> , 2016)	Deep flaws difficult to detect Depth of crack data are not provided Results are often influenced by conditions at the boundary, irregularities at the surface and atmospheric temperature
Electrical resistivity (Lataste <i>et al.</i> , 2003; Polder, 2001; Torres-Luque <i>et al.</i> , 2014)	Results are often confusing and difficult to analyse and interpret Pre-wetting process must be carried out on the surface Unavailability of road measurement system which are automated. Properties like salt content, porosity and moisture content have great influence on it
Chain drag and hammer sounding (Stanley and Balendran, 1994)	This can't be used on vertical surfaces Operator's hearing skills is highly required Initial delamination is not detected Ineffective on bridge decks with overlays

MATERIALS AND METHODS

Structural health monitoring: Structural Health Monitoring (SHM) refers to the studying of a structural system for a period of time and taking records of its responses with the use of equipment like arrays of sensors, Damage-Sensitive Features (DSFs) extraction and statistical analysis to detect changes that may result from structural damages (Farahani, 2013). SHM can also be defined as the measurement of the operating and loading environment and the critical responses of a structure to track and evaluate the symptoms of operational incidents, anomalies and/or deterioration or damage indicators that may affect operation, serviceability or safety reliability (Aktan *et al.*, 2000). It aims to give a diagnosis of the state of every element of a structure at every moment during the structure's lifetime. SHM combines a variety of sensing technologies configured to capture, log and analyse real-time data, its systems are designed to accurately study and test the health and performance of structures such as buildings, stadia, bridges, dams, wind turbines, aircrafts, ships, etc. SHM emphasizes on monitoring structural responses to the environment in real time (Yun *et al.*, 2003). The difference between NDT measurements and SHM is that NDT provides inspection into the structural geometry, response to load application, details of damage events, regions of damage initiation and stress point while SHM involves the use of sensors which are fixed permanently for routing checks at intervals (Habel, 2010). The two philosophies are related and at times both uses the same measurement physics. A major factor in

SHM is the in-service positioning of sensors and systems to maintain calibration when exposed to the elements over many months or years. Several researchers have carried out various study on SHM, spanning from laboratory work to full scale tests (Ragland *et al.*, 2011; Cheung *et al.*, 2008; Fasel *et al.*, 2002).

An early practice of SHM can be found in the aerospace industries which assessed the condition of materials and structural components by using Non-Destructive Evaluation (NDE) methods (Doebbling *et al.*, 1998). Fasel *et al.* (2002) worked on a three story building simulation using an electro dynamic shaker attached to the base of the structure, it was reported that sensors position in any assessment is important and can determine the effectiveness of the work done. Ragland *et al.* (2011) used a different approach in finite element analysis of a five-girder bridge subjected to vertical vibration source and reported difference in sensitivities of the horizontal response of the bridge and the vertical response. Cheung *et al.* (2008) used the triaxial vibration data of the Z24 Bridge, Kramer *et al.* (1999) obtained under the ambient loading and reported similarities in the results obtained using horizontal and vertical vibration data. Lucena and Dos Santos (2016) proposed a new approach for SHM in structural damage detection using both Time Reversal Method (TRM) and Spectral Element Method (SEM). Their methodology uses numerical simulation evaluation (MATLAB environment) to bring together time reversal signal processing and wave-based spectral element model. It was established that healthy and cracked rod models simulations gave

same acceleration response result with the literature also damage status and position can be revealed with the method.

Structural reliability theory: Structural reliability analysis on the other hand is concerned with the logical management of uncertainties in the design of structures (Thoft-Christensen and Baker, 1982; Afolayan and Opeyemi, 2010a, b). Structural reliability in a most general sense is the ability of a structure to fulfil its design purpose for some specified time and in a narrow sense (or mathematically) is the probability that a structure will not attain each specified limit state (ultimate or serviceability) during a specified reference period (Thoft-Christensen and Baker, 1982). This ability of a structure to fulfil its design purpose is measured on a fundamental basis of probability; the reliability of a structure can be said to be the probability of the structure performing to the purpose of its design according to some performance functions with respect to excessive conditions within a time frame (Afolayan and Opeyemi, 2010a, b). Methods that has been proposed for assessment of structural reliability are First Order Second Moment (FOSM) method (Afolayan and Opeyemi, 2010a, b; Akindahunsi and Afolayan, 2009; Wen, 2001), Advanced Second Moment (ASM) method and computer based Monte Carlo Simulation (MCS) (Ayyub, 1997).

Numerous researches have been done on reliability theory and applications, Akindahunsi and Afolayan (2009) worked on developed reliability-based interaction curves for design of reinforced concrete columns, the criteria of British Standard Code of Practice (1997) was examined. For established safety level to be maintained in designs, FORTRAN computer language was developed using British Standards Institute (1997) design requirements and the First Order Reliability Method (FORM).

RESULTS AND DISCUSSION

Previous analyses of SHM data: Acquisition of SHM data requires effective analyses and evaluation, researches carried out on SHM in the past have been interpreted in different ways.

From Table 2, researches done on SHM have been analysed in times past using graphical representations, table, numerical analysis, 3D images, statistical analysis and finite element methods, very small number of the researches are in terms of reliability-based paradigm. Researches that have employed reliability theory to analyse SHM data are researches on bridges (Ye *et al.*, 2018; Catbas *et al.*, 2008). There is need for researches into reinforced concrete buildings which will use reliability theory to analyse full SHM data.

Table 2: Different methods of analyses of SHM researches

Researchers	Analyses Methods	Types of test	Equipment used	Data taken
Garnal <i>et al.</i> (2013)	Graphical representations and table forms	Laboratory test of a structural model	Microprocessors, wireless communication, transducer and cellular transmission	Structural strain data
Skolnik <i>et al.</i> (2008)	Finite element method, illustrations	Real structure test	Eccentric mass shakers, tri-axial accelerometers, linear variable differential transducer	Interstory drift/ displacement data
Belostotsky and Akimov (2016)	Finite element method, illustrations	Computational assessment of load-bearing finite element model	Computer based	Stress-strain state and load-bearing capacity of structures
Roghaei and Zabihollah (2014)	Theoretical illustrations	Laboratory test of a structural model	Array of piezoelectric sensors	deformation and stress data
Hajdukiewicz <i>et al.</i> (2015)	Graphical and tabular presentations	Real structure test	Vibrating Wire (VW) gauges, Electrical Resistance (ER) strain gauges, IP68 rated thermistor sensors, BMS and indoor sensors, weather monitoring sensors, etc	Temperature data
Hosseinlou and Mojtahedi (2016)	Empirical modelling	Laboratory test of a structural model	Electric sensors	Column and beam modal measurements
Karayannis <i>et al.</i> (2016)	Graphical presentations	Laboratory test of a structural model	Piezoelectric sensors, linear variable differential transducer	Flexural response and deflection
Loutas <i>et al.</i> (2015)	Numerical analysis	Laboratory test	Fiber Optic Ribbon Tapes (FORTs)	Strain measurements
Comanducci <i>et al.</i> (2015)	Methods of multivariate statistical analysis	Laboratory test of a structural model	Multivariate statistical analysis tools	Wind speed and wind effect data
Lucena and Dos Santos (2016)	Numerical simulation	Computer based mdel	MATLAB, spectral element method	Frequency data
Lorenzoni <i>et al.</i> (2016)	Statistical models and algorithmic analysis	Real structure test	Traditional displacement transducers and optical camera	Crack data

CONCLUSION

For proper acknowledgement of SHM for assessment in structures there is a need for a reliability measure, similar to the probability of detection for NDI. Several questions must be answered for the actualization of SHM of structures such questions are:

- What are the economic and technical benefits?
- Is the approach validated?
- What is the false/positive call rate?
- What is the reliability of such a system?

Structural reliability approach has not been fully studied on reinforced concrete buildings using SHM data as the input. Most reliability methods make use of condition ratings based on visual inspections or theoretical/numerical models. There have been suggestions on supplementing reliability models with sensor data or non-destructive experimental results. A reliability approach using a complete SHM application needs to be further investigated. The integration of SHM and reliability analysis as a framework composed of a comprehensive structural health monitoring application for probabilistic analysis of buildings will foster efficient structural management and decision-making.

REFERENCES

- ACI Committee 228, 1998. Non-destructive Test Methods for Evaluation of Concrete in Structures. ACI 228. 2R-98, ACI., Farmington Hills, MI.
- ASTM., 1999. C 876-91: Standard test method for half-cell potentials of uncoated reinforcing steel in concrete (Withdrawn 2008). ASTM International, West Conshohocken, Pennsylvania. <https://www.astm.org/DATABASE.CART/HISTORICAL/C876-91R99.htm>
- ASTM., 2003. ASTM-C42: Standard test method for obtaining and testing drilled cores and sawed beams of concrete. ASTM International, West Conshohocken, Pennsylvania, USA. <https://standards.globalspec.com/std/895585/ASTM%20C42>
- ASTM., 2009. C597-09: Standard test method for pulse velocity through concrete. ASTM International, Philadelphia, Pennsylvania. <https://www.astm.org/DATABASE.CART/HISTORICAL/C597-09.htm>
- ASTMD., 1997. D 4580-86: Standard practice for measuring delaminations in concrete bridge decks by sounding. ASTM International, Philadelphia, Pennsylvania. <https://www.astm.org/DATABASE.CART/HISTORICAL/D4580-86R97.htm>
- Afolayan, J.O. and D.A. Opeyemi, 2010b. Reliability analysis of static pile capacity for concrete and steel in cohesionless soils. *Electron. J. Geotech. Eng.*, 15: 311-319.
- Afolayan, J.O. and D.A. Opeyemi, 2010a. Stochastic modeling of dynamic pile capacity using hiley, Janbu and gates formulae. *J. Sci. Multidiscip. Res.*, 2: 47-57.
- Afshari, A.A., D.G. Frazer and R.C. Creese, 1996. Ultrasonic Techniques for the Bonding of Rebar in Concrete Structures. In: *Structural Materials Technology-An NDT Conference*, Hartbower, P.E. and P.J. Stolarski (Eds.). Technomic Publishing Co. Inc., Lancaster, USA., ISBN:9781566764247, pp: 3-8.
- Akindahunsi, A.A. and J.O. Afolayan, 2009. Developed reliability-based interaction curves for design of reinforced concrete columns. *J. Theor. Appl. Mech.*, 47: 943-955.
- Aktan, A.E., F.N. Catbas, K.A. Grimmelsman and C.J. Tsikos, 2000. Issues in infrastructure health monitoring for management. *J. Eng. Mech.*, 126: 711-724.
- Alani, A.M., M. Aboutalebi and G. Kilic, 2013. Applications of Ground Penetrating Radar (GPR) in bridge deck monitoring and assessment. *J. Appl. Geophys.*, 97: 45-54.
- Alani, A.M., M. Aboutalebi and G. Kilic, 2014. Integrated health assessment strategy using NDT for reinforced concrete bridges. *NDT. E. Intl.*, 61: 80-94.
- Anonymous, 2001. BS EN 12504-2: British standard testing concrete in structures-Non-destructive testing, determination of rebound number. B.S.I. Standards Body, London, UK.
- Ayyub, B.M., 1997. *Uncertainty Modeling and Analysis in Civil Engineering*. CRC Press, Boca Raton, Florida, USA., ISBN:9780849331084, Pages: 528.
- Azari, H., S. Nazarian and D. Yuan, 2014. Assessing sensitivity of impact echo and ultrasonic surface waves methods for nondestructive evaluation of concrete structures. *Constr. Build. Mater.*, 71: 384-391.
- BSI., 1998. Eurocode 8, Design of structures for earthquake resistance-Part 3: Assessment and retrofitting of buildings. British Standard, UK. <http://civil.emu.edu.tr/courses/civ1471/1998-3-2005.pdf>
- Barnes, C.L. and J.F. Trottier, 2000. Ground-penetrating radar for network-level concrete deck repair management. *J. Trans. Eng.*, 126: 257-262.

- Barnes, C.L., J.F. Trottier and D. Forgeron, 2008. Improved concrete bridge deck evaluation using GPR by accounting for signal depth-amplitude effects. *NDT. E. Intl.*, 41: 427-433.
- Basu, A. and A. Aydin, 2004. A method for normalization of Schmidt hammer rebound values. *Intl. J. Rock Mech. Min. Sci.*, 41: 1211-1214.
- Bedon, C. and A. Morassi, 2014. Dynamic testing and parameter identification of a base-isolated bridge. *Eng. Struct.*, 60: 85-99.
- Behnia, A., H.K. Chai and T. Shiotani, 2014. Advanced structural health monitoring of concrete structures with the aid of acoustic emission. *Constr. Build. Mater.*, 65: 282-302.
- Belostotsky, A.M. and P.A. Akimov, 2016. Adaptive finite element models coupled with structural health monitoring systems for unique buildings. *Procedia Eng.*, 153: 83-88.
- Binda, L., A. Saisi and C. Tiraboschi, 2001. Application of sonic tests to the diagnosis of damaged and repaired structures. *NDT. E. Intl.*, 34: 123-138.
- Binda, L., A. Saisi, C. Tiraboschi, S. Valle and C. Colla *et al.*, 2003. Application of sonic and radar tests on the piers and walls of the Cathedral of Noto. *Constr. Build. Mater.*, 17: 613-627.
- Bogas, J.A., M.G. Gomes and A. Gomes, 2013. Compressive strength evaluation of structural lightweight concrete by non-destructive ultrasonic pulse velocity method. *Ultrason.*, 53: 962-972.
- Breyse, D., 2012. Nondestructive evaluation of concrete strength: An historical review and a new perspective by combining NDT methods. *Constr. Build. Mater.*, 33: 139-163.
- British Standards Institute, 1997. British Standard for Structural use of Concrete, Code of Practice for Design and Construction. BSI, London, UK.
- Buyukozturk, O., 1998. Imaging of concrete structures. *NDT. E. Intl.*, 31: 233-243.
- Caetano, E., A. Cunha, C. Moutinho and W. Hu, 2015. Dynamic monitoring of civil engineering structures. Proceedings of the 2015 3rd International Conference on Experiment (exp. At'15), June 2-4, 2015, IEEE, Ponta Delgada, Portugal, pp: 79-85.
- Carlos, M.F., P.T. Cole, S.J. Vahaviolos and T. Halkyard, 2000. Acoustic Emission Bridge Inspection/Monitoring Strategies. In: *Structural Materials Technology IV: An NDT Conference*, Alampalli, S. (Ed.). CRC Press, Boca Raton, Florida, USA., ISBN:9781566769495, pp: 179-183.
- Casas, J.R. and J.D. Gomez, 2013. Load rating of highway bridges by proof-loading. *KSCE. J. Civil Eng.*, 17: 556-567.
- Catbas, F.N., M. Susoy and D.M. Frangopol, 2008. Structural health monitoring and reliability estimation: Long span truss bridge application with environmental monitoring data. *Eng. Struct.*, 30: 2347-2359.
- Cawley, P. and R.D. Adams, 1988. The mechanics of the coin-tap method of non-destructive testing. *J. Sound Vibr.*, 122: 299-316.
- Cawley, P., 1991. A high frequency coin-tap method of non-destructive testing. *Mech. Syst. Signal Proc.*, 5: 1-11.
- Chang, C.W., C.H. Lin and H.S. Lien, 2009. Measurement radius of reinforcing steel bar in concrete using digital image GPR. *Constr. Build. Mater.*, 23: 1057-1063.
- Chang, P.C., A. Flatau and S.C. Liu, 2003. Health monitoring of civil infrastructure. *Struct. Health Monit.*, 2: 257-267.
- Cheng, C. and M. Sansalone, 1993. The impact-echo response of concrete plates containing delaminations: Numerical, experimental and field studies. *Mater. Struct.*, 26: 274-285.
- Cheung, A., C. Cabrera, P. Sarabandi, K.K. Nair and A. Kiremidjian *et al.*, 2008. The application of statistical pattern recognition methods for damage detection to field data. *Smart Mater. Struct.*, 17: 1-12.
- Clark, M.R., D.M. McCann and M.C. Forde, 2009. Application of infrared thermography to the non-destructive testing of concrete and masonry bridges. *NDT. E. Intl.*, 36: 265-275.
- Clemea, G.G., D.R. Jackson and G.C. Crawford, 1992. Benefits of using half-cell potential measurements in condition surveys of concrete bridge decks. *Trans. Res. Rec.*, 1347: 46-55.
- Colla, C., P.C. Das, D. McCann and M.C. Forde, 1997. Sonic, electromagnetic and impulse radar investigation of stone masonry bridges. *NDT. E. Intl.*, 30: 249-254.
- Comanducci, G., F. Ubertini and A.L. Materazzi, 2015. Structural health monitoring of suspension bridges with features affected by changing wind speed. *J. Wind Eng. Ind. Aerodyn.*, 141: 12-26.
- Cunha, A., E. Caetano, F. Magalhaes and C. Moutinho, 2013. Recent perspectives in dynamic testing and monitoring of bridges. *Struct. Control Health Monit.*, 20: 853-877.
- Davis, A.G., 2003. The nondestructive impulse response test in North America: 1985-2001. *NDT. E. Intl.*, 36: 185-193.

- De Roeck, G., B. Peeters and J. Maeck, 2000. Dynamic monitoring of civil engineering structures. Proceedings of the IASS-IACM 2000 Abstracts 4th International Conference on Colloquium on Computation of Shell & Spatial Structures, June 4-7, 2000, Chania-Crete, Greece, pp: 1-4.
- Diamanti, N., A. Giannopoulos and M.C. Forde, 2008. Numerical modelling and experimental verification of GPR to investigate ring separation in brick masonry arch bridges. *NDT. E. Intl.*, 41: 354-363.
- Doebbling, S.W., C.R. Farrar and M.B. Prime, 1998. A summary review of damage identification methods that examine changes in dynamic properties. *Shock Vibration Digest*, 30: 91-105.
- Elsener, B., 2001. Half-cell potential mapping to assess repair work on RC structures. *Const. Build. Mater.*, 15: 133-139.
- Elsener, B., C. Andrade, J. Gulikers, R. Polder and M. Raupach, 2003b. Half-cell potential measurements-potential mapping on reinforced concrete structures. *Mater. Struct.*, 36: 461-471.
- Elsener, B., L. Zimmermann and H. Bohni, 2003a. Non destructive determination of the free chloride content in cement based materials. *Mater. Corros.*, 54: 440-446.
- Estes, A.C. and D.M. Frangopol, 2003. Updating bridge reliability based on bridge management systems visual inspection results. *J. Bridge Eng.*, 8: 374-382.
- Faber, M.H., D.V. Val and M.G. Stewart, 2000. Proof load testing for bridge assessment and upgrading. *Eng. Struct.*, 22: 1677-1689.
- Farahani, R.V., 2013. Structural health monitoring and damage identification of bridges using triaxial geophones and time series analysis. Ph.D Thesis, The University of Tennessee, Knoxville, Tennessee.
- Farrar, C.R. and K. Worden, 2006. An introduction to structural health monitoring. *Philos. Trans. R. Soc. A. Math. Phys. Eng. Sci.*, 365: 303-315.
- Fasel, T.R., S.W. Gregg, T.J. Johnson, C.R. Farrar and H. Sohn, 2002. Experimental modal analysis and damage detection in a simulated three story building. Proceedings of the 20th IMAC Conference on Structural Dynamics, February 01, 2002, Society for Experimental Mechanics, Los Angeles, California, USA., pp: 590-595.
- Fu, G. and J. Tang, 1995. Risk-based proof-load requirements for bridge evaluation. *J. Struct. Eng.*, 121: 542-556.
- Gamal, A., A. ElSafty and G. Merckel, 2013. New system of structural health monitoring. *Open J. Civil Eng.*, 3: 19-28.
- Garboczi, E.J., L.M. Schwartz and D.P. Bentz, 1995. Modeling the influence of the interfacial zone on the DC electrical conductivity of mortar. *Adv. Cem. Based Mater.*, 2: 169-181.
- Gattulli, V. and L. Chiaramonte, 2005. Condition assessment by visual inspection for a bridge management system. *Comput. Aided Civil Infrastruct. Eng.*, 20: 95-107.
- Gentile, C., 2006. Modal and structural identification of a RC arch bridge. *Struct. Eng. Mech.*, 22: 53-70.
- Gucunski, N. and NRC., 2013. *Nondestructive Testing to Identify Concrete Bridge Deck Deterioration*. Transportation Research Board, Washington, D.C., USA., ISBN:9780309129336, Pages: 85.
- Habel, W.R., 2010. *Structural Health Monitoring Systems for Reinforced Concrete Structures*. In: *Non-Destructive Evaluation of Reinforced Concrete Structures: Non-Destructive Testing Methods*, Maierhofer, C., H.W. Reinhardt and G. Dobmann (Eds.). Woodhead Publishing, Sawston, UK., ISBN:9781845699604, pp: 63-94.
- Hajdukiewicz, M., D. Byrne, M.M. Keane and J. Goggins, 2015. Real-time monitoring framework to investigate the environmental and structural performance of buildings. *Build. Environ.*, 86: 1-16.
- Hashim, H., Z. Ibrahim and H.A. Razak, 2013. Dynamic characteristics and model updating of damaged slab from ambient vibration measurements. *Meas.*, 46: 1371-1378.
- Holford, K.M. and R.J. Lark, 2005. *Acoustic Emission Testing of Bridges: Inspection and Monitoring Techniques for Bridges and Structures*. Woodhead Publishing Ltd., Cambridge, UK.,
- Holford, K.M., A.W. Davies, R. Pullin and D.C. Carter, 2001. Damage location in steel bridges by acoustic emission. *J. Intell. Mater. Syst. Struct.*, 12: 567-576.
- Holicky, M., V. Navarova, R. Gottfried and M. Kronika, 2014. *Basics for Assessment of Existing Structures*. 1st Edn., Klokner Institute, Czech Technical University in Prague, Prague, Czechia, ISBN:978-80-01-05420-8, Pages: 109.
- Hosseiniou, F. and A. Mojtahedi, 2016. Developing a robust simplified method for structural integrity monitoring of offshore jacket-type platform using recorded dynamic responses. *Appl. Ocean Res.*, 56: 107-118.
- Hugenschmidt, J. and R. Mastrangelo, 2006. GPR inspection of concrete bridges. *Cem. Concr. Compos.*, 28: 384-392.
- Ibrahim, M.E., 2014. Nondestructive evaluation of thick-section composites and sandwich structures: A review. *Compos. Part A. Appl. Sci. Manuf.*, 64: 36-48.

- Ibrahim, M.E., 2016. Nondestructive Testing and Structural Health Monitoring of Marine Composite Structures. In: Marine Applications of Advanced Fibre-Reinforced Composites, Graham-Jones, J. and J. Summerscales (Eds.). Woodhead Publishing, Sawston, Cambridge, UK., ISBN:9781782422501, pp: 147-183.
- Ismail, Z., Z. Ibrahim, A.Z.C. Ong and A.G.A. Rahman, 2011. Approach to reduce the limitations of modal identification in damage detection using limited field data for nondestructive structural health monitoring of a cable-stayed concrete bridge. *J. Bridge Eng.*, 17: 867-875.
- Jain, A., A. Kathuria, A. Kumar, Y. Verma and K. Murari, 2013. Combined use of non-destructive tests for assessment of strength of concrete in structure. *Procedia Eng.*, 54: 241-251.
- Karayannis, C.G., C.E. Chalioris, G.M. Angeli, N.A. Papadopoulos and M.J. Favvata *et al.*, 2016. Experimental damage evaluation of reinforced concrete steel bars using piezoelectric sensors. *Constr. Build. Mater.*, 105: 227-244.
- Kim, J.K., C.Y. Kim, S.T. Yi and Y. Lee, 2009. Effect of carbonation on the rebound number and compressive strength of concrete. *Cem. Concr. Compos.*, 31: 139-144.
- Kramer, C., C.A.M. de Smet and G. de Roeck, 1999. Z24 bridge damage detection tests. Proceedings of the 17th International Conference on Modal Analysis (IMAC 1999) Vol. 3727, February 01, 1999, Society of Photo-optical Instrumentation Engineers, Kissimmee, Florida, pp: 1023-1029.
- Langenberg, K.J., K. Mayer and R. Marklein, 2010. Non-Destructive Testing of Concrete with Electromagnetic, Acoustic and Elastic Waves: Modelling and Imaging. In: Non-Destructive Evaluation of Reinforced Concrete Structures: Non Destructive Testing Methods, Maierhofer, C., H. W. Reinhardt and G. Dobmann (Eds.). Woodhead Publishing, Sawston, UK., ISBN:9781439841129, pp: 144-162.
- Lataste, J.F., C. Sirieix, D. Breysse and M. Frappa, 2003. Electrical resistivity measurement applied to cracking assessment on reinforced concrete structures in civil engineering. *NDT. E. Intl.*, 36: 383-394.
- Lin, J.M. and M. Sansalone, 1993. The transverse elastic impact response of thick hollow cylinders. *J. Nondestr. Eval.*, 12: 139-149.
- Lin, J.M. and M. Sansalone, 1994. Impact-echo response of hollow cylindrical concrete structures surrounded by soil and rock: Part I-numerical studies. *Geotech. Test J.*, 17: 207-219.
- Lin, J.M. and M. Sansalone, 1996. Impact-echo studies of interfacial bond quality in concrete: Part I-effects of unbonded fraction of area. *Mater. J.*, 93: 223-232.
- Lin, Y. and W.C. Su, 1996. Use of stress waves for determining the depth of surface-opening cracks in concrete structures. *Mater. J.*, 93: 494-505.
- Lorenzoni, F., F. Casarin, M. Caldon, K. Islami and C. Modena, 2016. Uncertainty quantification in structural health monitoring: Applications on cultural heritage buildings. *Mech. Syst. Signal Process.*, 66: 268-281.
- Loutas, T.H., P. Charlaftis, A. Airoidi, P. Bettini and C. Koimtzoglou *et al.*, 2015. Reliability of strain monitoring of composite structures via the use of optical fiber ribbon tapes for structural health monitoring purposes. *Compos. Struct.*, 134: 762-771.
- Lucena, R.L. and J.M.C. Dos Santos, 2016. Structural health monitoring using time reversal and cracked rod spectral element. *Mech. Syst. Signal Process.*, 79: 86-98.
- Maierhofer, C., C. Kohl and J. Wostmann, 2010. Combining the Results of Various Non-Destructive Evaluation Techniques for Reinforced Concrete: Data Fusion. In: Non-Destructive Evaluation of Reinforced Concrete Structures: Non-Destructive Testing Methods, Maierhofer, C., H.W. Reinhardt and G. Dobmann (Eds.). Woodhead Publishing, Sawston, UK., ISBN:9781439841129, pp: 95-107.
- Malhotra, V.M., 1976. Testing Hardened Concrete: Nondestructive Methods. Iowa State University Press, Iowa, USA., ISBN:9780813811550, Pages: 188.
- Mandache, C., M. Genest, M. Khan and N. Mrad, 2011. Considerations on structural health monitoring reliability. Proceedings of the International Workshop on Smart Materials, Structures & NDT in Aerospace, November 2-4, 2011, Montreal, Quebec, Canada, pp: 1-10.
- McCann, D.M. and M.C. Forde, 2001. Review of NDT methods in the assessment of concrete and masonry structures. *NDT. E. Intl.*, 34: 71-84.
- Naik, T.R., V.M. Malhotra and J.S. Popovics, 2004. The Ultrasonic Pulse Velocity Method. In: Handbook on Nondestructive Testing of Concrete, Malhotra, V.M. and N.J. Carino (Eds.). CRC Press, Boca Raton, New York, USA., ISBN:9780803120990, pp: 8-1-8-14.
- Ohtsu, M., T. Yamamoto and K. Matsuyama, 1997. Quantitative NDE estimation for rebar corrosion in concrete. Proceedings of the 7th International Conference on Structural Faults and Repair Concrete and Composites Vol. 2, July 8, 1997, Edinburgh, UK., pp: 265-273.

- Orlando, L., A. Pezone and A. Colucci, 2010. Modeling and testing of high frequency GPR data for evaluation of structural deformation. *NDT. E. Intl.*, 43: 216-230.
- Park, S., N. Stubbs, R. Bolton, S. Choi and C. Sikorsky, 2001. Field verification of the damage index method in a concrete box-der bridge via visual inspection. *Comput. Aided Civil Infrast. Eng.*, Q 16: 58-70.
- Perenchio, W.F., 1989. The condition survey. *Concr. Intl.*, 11: 59-62.
- Perez-Gracia, V., F.G. Garcia and I.R. Abad, 2008. GPR evaluation of the damage found in the reinforced concrete base of a block of flats: A case study. *NDT. E. Intl.*, 41: 341-353.
- Polder, R.B., 2001. Test methods for on site measurement of resistivity of concrete-a RILEM TC-154 technical recommendation. *Constr. Build. Mater.*, 15: 125-131.
- Ragland, W.S., D. Penumadu and R.T. Williams, 2011. Finite element modeling of a full-scale five-girder bridge for structural health monitoring. *Struct. Health Monit.*, 10: 449-465.
- Rehman, S.K.U., Z. Ibrahim, S.A. Memon and M. Jameel, 2016. Nondestructive test methods for concrete bridges: A review. *Constr. Build. Mater.*, 107: 58-86.
- Rens, K.L., T.J. Wipf and F.W. Klaiber, 1997. Review of nondestructive evaluation techniques of civil infrastructure. *J. Perform. Constr. Facil.*, 11: 152-160.
- Reynolds, P., 2008. Dynamic testing and monitoring of civil engineering structures. *Exp. Tech.*, 32: 54-57.
- Roghaei, M. and A. Zabihollah, 2014. An efficient and reliable structural health monitoring system for buildings after Earthquake. *APCBEE. Procedia*, 9: 309-316.
- Ryan, E., E. Burdette, R. Ankabrandt, R. Nidiffer and B. Buchanan, 2013. Comparison of two methods to assess the resistance of concrete to chloride ion penetration. *J. Mater. Civil Eng.*, 26: 698-704.
- Sadowski, L., J. Hola and S. Czarniecki, 2016. Non-destructive neural identification of the bond between concrete layers in existing elements. *Constr. Build. Mater.*, 127: 49-58.
- Salawu, O.S. and C. Williams, 1995. Review of full-scale dynamic testing of bridge structures. *Eng. Struct.*, 17: 113-121.
- Saleem, M., M. Shameem, S.E. Hussain and M. Maslehuddin, 1996. Effect of moisture, chloride and sulphate contamination on the electrical resistivity of Portland cement concrete. *Constr. Build. Mater.*, 10: 209-214.
- Samman, M.M. and M. Biswas, 1994. Vibration testing for nondestructive evaluation of bridges I: Theory. *J. Struct. Eng.*, 120: 269-289.
- Samman, M.M. and M. Biswas, 1994. Vibration testing for nondestructive evaluation of bridges II: Results. *J. Struct. Eng.*, 120: 290-306.
- Sansalone, M., 1997. Impact-echo: The complete story. *Struct. J.*, 94: 777-786.
- Sansalone, M.J. and W.B. Street, 1997. *Impact-Echo: Non Destructive Evaluation of Concrete and Masonry*. Bulbriers Press, Ithaca, New York, USA.
- Saraf, V., A.F. Sokolik and A.S. Nowak, 1996. Proof load testing of highway bridges. *Trans. Res. Rec. J. Trans. Res. Board*, 1541: 51-57.
- Schickert, M., 2005. Progress in ultrasonic imaging of concrete. *Mater. Struct.*, 38: 807-815.
- Scott, M., A. Rezaizadeh, A. Delahaza, C.G. Santos and M. Moore *et al.*, 2003. A comparison of nondestructive evaluation methods for bridge deck assessment. *NDT. E. Intl.*, 36: 245-255.
- Shah, A.A., Y. Ribakov and C. Zhang, 2013. Efficiency and sensitivity of linear and non-linear ultrasonics to identifying micro and macro-scale defects in concrete. *Mater. Des.*, 50: 905-916.
- Shaw, P. and A. Xu, 1997. Assessment of the deterioration of concrete in NPP-causes, effects and investigative methods. *Proceedings of the Joint EC OECD IAEA Specialists Meeting Vol. 3, March 11-13, 1997, Helsingborg, Sweden*, pp: 1-13.
- Shokouhi, P., J. Wolf and H. Wiggenhauser, 2013. Detection of delamination in concrete bridge decks by joint amplitude and phase analysis of ultrasonic array measurements. *J. Bridge Eng.*, 19: 04013005-04013005.
- Skolnik, D.A., W.J. Kaiser and J.W. Wallace, 2008. Instrumentation for structural health monitoring: Measuring interstory drift. *Proceedings of the 14th World Conference on Earthquake Engineering, October 12-17, 2008, Beijing, China*, pp: 1-8.
- Solla, M., H. Lorenzo, A. Novo and J.C. Caamano, 2012. Structural analysis of the Roman Bibei bridge (Spain) based on GPR data and numerical modelling. *Autom. Constr.*, 22: 334-339.
- Song, H.W. and V. Saraswathy, 2007. Corrosion monitoring of reinforced concrete structures-A review. *Int. J. Electrochem. Sci.*, 2: 1-28.
- Stanley, C.C. and R.V. Balendran, 1994. Developments in assessing the structural integrity of applied surfaces to concrete buildings. *Struct. Surv.*, 12: 4-9.
- Suzuki, T., H. Ogata, R. Takada, M. Aoki and M. Ohtsu, 2010. Use of acoustic emission and X-ray computed tomography for damage evaluation of freeze-thawed concrete. *Constr. Build. Mater.*, 24: 2347-2352.

- Szilagyi, K., A. Borosnyoi and I. Zsigovics, 2011. Rebound surface hardness of concrete: Introduction of an empirical constitutive model. *Constr. Build. Mater.*, 25: 2480-2487.
- Taffe, A. and H. Wiggerhauser, 2006. Validation for thickness measurement in civil engineering with ultrasonic echo. Proceedings of the 9th European Conference on NDT: ECNDT, September 25-29, 2006, DGZfP, Berlin, Germany, pp: 1-8.
- Thoft-Christensen, P. and M.J. Baker, 1982. *Structural Reliability Theory and its Applications*. Springer, Berlin, Germany, ISBN:978-3-642-68697-9, Pages: 268.
- Torres-Luque, M., E. Bastidas-Arteaga, F. Schoefs, M. Sanchez-Silva and J.F. Osmá, 2014. Non-destructive methods for measuring chloride ingress into concrete: State-of-the-art and future challenges. *Constr. Build. Mater.*, 68: 68-81.
- Tortora, M., S. Sfarra, M. Chiarini, V. Daniele and G. Taglieri *et al.*, 2016. Non-destructive and micro-invasive testing techniques for characterizing materials, structures and restoration problems in mural paintings. *Appl. Surf. Sci.*, 387: 971-985.
- Turner, M.J., 1997. *Integrity Testing in Piling Practice*. Vol. 144, CIRIA, London, UK., ISBN:9780860174738, Pages: 336.
- Wankhade, R.L. and A.B. Landage, 2013. Non-destructive testing of concrete structures in Karad region. *Procedia Eng.*, 51: 8-18.
- Wen, Y.K., 2001. Reliability and performance-based design. *Struct. Safety*, 23: 407-428.
- Whittington, H.W., J. McCarter and M.C. Forde, 1981. The conduction of electricity through concrete. *Mag. Concr. Res.*, 33: 48-60.
- Wu, H. and M. Siegel, 1999. Correlation of accelerometer and microphone data in the coin tap test. Proceedings of the 16th IEEE International Conference on Instrumentation and Measurement Technology IMTC/99 (Cat. No. 99CH36309), May 24-26, 1999, IEEE, Venice, Italy, pp: 814-819.
- Ye, X.W., P.S. Xi, Y.H. Su, B. Chen and J.P. Han, 2018. Stochastic characterization of wind field characteristics of an arch bridge instrumented with structural health monitoring system. *Struct. Safety*, 71: 47-56.
- Yehia, S., N. Qaddoumi, S. Farrag and L. Hamzeh, 2014. Investigation of concrete mix variations and environmental conditions on defect detection ability using GPR. *NDT. E. Intl.*, 65: 35-46.
- Yun, C.B., J.J. Lee, S.K. Kim and J.W. Kim, 2003. Recent R&D activities on structural health monitoring for civil infra-structures in Korea. *KSCE. J. Civil Eng.*, 7: 637-651.